

Hazardous Class

Name	HZD.570-2
Reference	833607
EAN code	5028965355886
Power supply	
Power supply type	230v AC 50/60Hz
Rated Motor Power	2 x 1000W
Protection class	Class I
Airflow Motor only	96 L/sec
Max Sealed Suction H ₂ O	2500mm
Max Air Flow (Motor Only)	346 m ³ /h
Max Air Flow (In Product)	184 m ³ /h
MAX Under Pressure	245 (hPa)
Low Flow Operation	22L/sec (1.32m ³ /min)
(NB 22L/sec corresponds to an airspeed of 20m/sec in a 38mm pipe)	
Sound Pressure (LpA)	67 dB (A)
Uncertainty (KpA)	0.5 dB
Cable length	10m
Cleaning Range	26.4m
Cable Type	HO5VV-F
NUPLUG system	Yes
Capacity / Weight Size	
Drum Capacity (DRY)	23.0L
Weight (Ready to Work)	20.36kg
Packed Weight	24.0kg
Width	415mm
Length	415mm
Height	746mm
Filtration	
Hazardous Class (EN60335-2-69)	H Class
Filter Type (901649 Cartridge)	H13 (EN1822)
Hepa Dust Bag	NVM-3BH
Filter	TriTex
Kit BB19 607349	
602102 2.4m NuFlex Threaded Hose	
604017 10 x (NVM-3BH Hepa/Flo Dust Bags	
602161 152mm Rubber Brush Soft Bristles (NVM-61B)	
602257 65mm Soft Dusting Brush with 38mm Adaptor	
908229 Roll of 10 x 120L Waste Bags (700 x 1100mm), Grey	
602160 305mm ABS Crevice Tool	
602923 280mm Stainless Steel Gulper/Scraper Tool (38mm)	
604116 Primary Permatex Filter for 356mm Machine	



DRY VACUUM

In the selection of any dust control machine, it is **vitaly important** that the size, power and capacity are given **serious consideration** from the outset, as the right choice will play an important and on-going part in **terms of user satisfaction**.

The 570 series provides a choice of Simplex one motor or Duplex two motor models

Advanced Filtration

Built to Last

Powerful & Efficient

Clean for Longer

Easy Clean & Safe Emptying

H CLASS



Suitable for:-
Asbestos.

These are suggested possible uses.
Check local H&S/Statutory regulations for the type of machine required for a specific use or dust type in your area /country as regulations may differ.

DRY

Specification subject to change without prior notice