

Hazardous Class

Name	HZ.570-2 (INDUSTRIAL)
Reference	833597
EAN code	05028965338421
Power supply	
Power supply type	120v AC 50/60Hz
Rated Motor Power	960W
Protection class	Class I
Airflow Motor only	48 L/sec
Max Sealed Suction H ² O	2500mm
Max Air Flow (Motor Only)	173 m ³ /h
Max Air Flow (In Product)	119 m ³ /h
MAX Under Pressure	260 (hPa)
Low Flow Operation	16L/sec (0.96m ³ /min)
(NB 16L/sec corresponds to an airspeed of 20m/sec in a 32mm pipe)	
Sound Pressure (LpA)	65 + dB (A)
Uncertainty (KpA)	0.5 dB
Cable length	10m
Cleaning Range	26.8m
Cable Type	HO5VV-F
NUPLUG system	Yes
Capacity / Weight Size	
Drum Capacity (DRY)	23.0L
Weight (Ready to Work)	18.16kg
Packed Weight	22.40kg
Width	415mm
Length	415mm
Height	746mm
Filtration	
Hazardous Class (EN60335-2-69)	H Class
Filter Type (901649 Cartridge)	H13 (EN1822)
Hepa Dust Bag	NVM-3BH
Filter	TriTex
Kit AA19 (2.2P)	
915907 Parallel Hose 32mm (BoFlex) 2.2m	
602161 152mm Rubber Brush Soft Bristles (NVM-61B)	
602159 38/32mm Adaptor (NVB-59B)	
601141 Double Taper hose/ Tool Adaptor	
601142 240mm Crevice Tool	
601144 65mm Soft Dusting Brush	
601917 280mm Stainless Steel Gulper/Scraper Tool (NVA-17B)	
604017 10 x (NVM-3BH Hepa/Flo Dust Bags	
908229 Roll of 10 x 120L Waste Bags (700 x 1100mm), Grey	
604116 Primary Permatex Filter for 356mm Machine	

Specification subject to change without prior notice



Certified
HEPA13
Filtration

DRY VACUUM

In the selection of any dust control machine, it is vitally important that the size, power and capacity are given serious consideration from the outset, as the right choice will play an important and on-going part in terms of user satisfaction.

The 570 series provides a choice of Simplex one motor or Duplex two motor models

- Advanced Filtration**
- Built to Last**
- Powerful & Efficient**
- Clean for Longer**
- Easy Clean & Safe Emptying**

H CLASS



Suitable for:-
Asbestos.

These are suggested possible uses. Check local H&S/Statutory regulations for the type of machine required for a specific use or dust type in your area /country as regulations may differ.

DRY