Numete

TECHNICAL SHEET

Hazardous Class

Name	HZ.900-2
Reference	833601
EAN code	05028965339602
Power supply	
Power supply type	230v AC 50/60Hz
Rated Motor Power	960W
Protection class	Class I
Airflow Motor only	48 L/sec
Max Sealed Suction H ² 0	2500mm
Max Air Flow (Motor Only)	173 m3/h
Max Air Flow (In Product)	119 m3/h
MAX Under Pressure	260 (hPa)
Low Flow Operation	16L/sec (0.96m3/min)
(NB 16L/sec corresponds to an airspeed of 20m/sec in a	
32mm pipe)	
Sound Pressure (LpA)	65 + dB (A)
Uncertainty (KpA) Cable length	0.5 dB 10m
Cleaning Range	26.8m
Cable Type	HO5VV-F
NUPLUG system	Yes
Capacity / Weight Size	100
Drum Capacity (DRY)	40.0L
Weight (Ready to Work)	29.6kg
Packed Weight	N/A
Width	490mm
Length	800mm
Height	880mm
Filtration	
Hazardous Class (EN60335-2-69)	H CLass
Filter Type (901649 Cartridge)	H13 (EN1822)
Hepa Dust Bag	NVM-4BH
Filter	TriTex
Kit AA20 (2.2P)	
915907 Parallel Hose 32mm (BoFlex) 2.2m	
602161 152mm Rubber Brush Soft Bristles (NVM-61B)	
602159 38/32mm Adaptor (NVB-59B)	
601141 Double Taper hose/ Tool Adaptor	
601142 240mm Crevice Tool	
601144 65mm Soft Dusting Brush	
601917 280mm Stainless Steel Gulper/Scraper Tool (NVA-17B)	
604019 10 x (NVM-4BH Hepa/Flo Dust Bags	
908229 Roll of 10 x 120L Waste Bags (700 x 1100mm), Grey	
604116 Primary Permatex Filter for 356mm Machine	
Specification subject to change without prior notice	



DRY VACUUM

In the selection of any dust control machine, it is vitally

important that the size, power and capacity are given serious consideration from the outset, as the right choice will play an important and on-going part in terms of user satisfaction.

The 900 series provides a choice of Simplex one motor or Duplex two motor models

Advanced Filtration

Built to Last Powerful & Efficient

CLASS

Clean for Longer Easy Clean & Safe Emptying

H CLASS

Suitable for:-Asbestos.

These are suggested possible uses. Check local H&S/Statutory regulations for the type of machine required for a specific use or dust type in your area /country as regulations may differ.



Specification subject to change without prior notice