

TRADELINE

Name	TEL390S-11
Reference	909051
EAN code	05028965780909
Power supply	
Power supply type	230v AC 50/60Hz
Rated Motor Power	620W
Protection class	Class II
Airflow Motor only	48 L/sec
Max Suction H ² O	2300mm
Sound Pressure	LpA ≤ 70.2 dB (A) (LpA)
Sound Pressure Uncertainty	0.5 dB (KpA)
MAX Under Pressure	206.5 Mbar 206.5 (hPa)
Max Flow Rate	29 L/s 104.4 m ³ /h
Cable length	10m
Cleaning Range	28.0m
Cable Type	HO5VV-F
NUPLUG system	Yes
Capacity / Weight Size	
Drum Capacity (DRY)	18L
Weight (Ready to Work)	10.8kg
Packed Weight	13.04kg
Width	400mm
Length	450mm
Height	600mm
Filtration	
Hazardous Class (EN60335-2-69)	L Class
Filter Type (901649 Cartridge)	H13 (EN1822)
Hepa Dust Bag	NVM-2BH
Filter	TriTex
Kit AS10 (Included Accessories)	
601008 Stainless Steel Extension Tube x2	
601052 Stainless Steel Tube Bend with NPC	
914762 2.8m Nuflex Hose	
900918 300mm Multiflo Dry Brush Tool	
601430 290mm Free Flo Floor Tool	
601141 Double Taper hose/ Tool Adaptor	
601142 240mm Crevice Tool	
601144 65mm Soft Dusting Brush	
601145 150mm Upholstery Tool	
601146 150mm Slide-on Brush for Upholstery Tool	
601176 Multi Size Power Tool Adaptor	



DRY VACUUM

Compact, tough and highly mobile, the TradeLine vacuum combines a specialist on tool extractor with a big clean-up machine to cover almost any application.

With more and more emphasis being put on health and safety within the construction industry, the demand for extraction vacuums increases year on year, this is where the TradeLine Range comes in.

Industrial Use

Built to Last

Powerful & Efficient

Industrial Use

L CLASS



Suitable for:-
General dust, Mixed Dust or Gypsum.

These are suggested possible uses. Check local H&S/Statutory regulations for the type of machine required for a specific use or dust type in your area /country as regulations may differ.

DRY

Specification subject to change without prior notice